LuXLuminaire Lighting solutions
A MIR GROUP COMPANY

PRODUCT DATASHEET
LS-LPM-72S-20 / 100-24
REV. 2026-11-12



SOLAR STREET LIGHTS · ALL-IN-TWO SOLAR STREET LIGHTS

All-in-Two Solar Street Light 20W · 2800 lm

Separate panel and luminaire for higher outputs and better panel orientation at high latitudes.

POWER **20 W**	LUMINOUS FLUX **2800 lm**	EFFICACY **140 lm/W**	SOLAR PANEL **100 Wp mono**
BATTERY **24 Ah**	INGRESS **IP65**	IMPACT **IK09**	COLOUR TEMP. **6500 K**

Applications Roads & highways · Rural & village roads · Off-grid & remote sites

Product summary

Product Code	LS-LPM-72S-20 / 100-24	**Luminaire Power**	20 W
Luminous Flux	2800 lm	**Solar Panel**	100 Wp monocrystalline PERC
LED Brands	3030 SMD LED	**Driver**	ENEC-certified LED drivers
Charge Controller	10 A MPPT	**Standards Compliance**	EN 60598-2-3, LM-80, TM-21

Production can be tailored to special demands.

Technical specifications

SOLAR ENERGY SYSTEM SPECIFICATIONS

Solar Panel Power	100 Wp monocrystalline PERC
Solar Panel Life Span	25 years
System Voltage	12.8 V DC
Charge Controller	10 A MPPT
Battery Type	32700 LiFePO4
Battery Capacity	24 Ah, 307.2 Wh
Battery Life Span	3000 cycles with 80% discharge

MECHANICAL & DIMENSIONS

Housing	Aluminium
IP Rating	IP65
IK Rating	IK09
RAL Code	7016
Operating Temperature	-30°C / +50°C
Energy and Luminaire Dimensions	800 × 680 × 150 mm / 210 × 345 × 70 mm
Luminaire Weight	13.5 kg
Console Length	700 mm
Packing Dimensions & Weight	820 × 700 × 160 mm / 15.0 kg

ELECTRICAL SPECIFICATIONS

Luminaire Power	20 W
Efficacy (lm/W)	140 lm/W
Luminous Flux	2800 lm
Light Source	3030 LED
Driver Type	ENEC-certified LED driver
Motion Sensor	Yes / Microwave
Class	III

OPTICAL SPECIFICATIONS

Light Distribution	Asymmetric
Diffuser	4 mm Tempered glass (Luminaire Front face)
Colour Temperature (CCT)	6500 K
CRI	>70

OPTIONS

✓ Step Dim | ✓ RAL Code | ✓ Autonomous Time | ✓ Colour Temperature: 3000 K / 4000 K / 5000 K / 5700 K | ✓ CRI: > 80 | ✓ Remote Control: Wi-Fi

Standards & certifications

TSE | CE | EAC | ENEC | EMC | IP65 | IK09 | Class III

Standards compliance: EN 60598-2-3, LM-80, TM-21

Full product page and quotation request: **https://solarstreetlighting.net/en/products/solar-street-lights/all-in-two/all-in-one-two-solar-road-and-street-luminaire-20w-2800-lm/**