LuXLuminaire Lighting solutions
A MIR GROUP COMPANY

PRODUCT DATASHEET
REV. 2026-11-12



LED FLOODLIGHTS · M-SERIES FLOODLIGHTS

M-Series Floodlight 3M

M-series modular floodlights with one to four LED modules.

POWER **120–150 W**	LUMINOUS FLUX **13200–19500 lm**	EFFICACY **110–130 lm/W**	INGRESS **IP66**
IMPACT **IK09**	COLOUR TEMP. **3000 K / 4000 K / 6500 K**	LED LIFE **50,000 hours**	ELECTRICAL CLASS **Class I / Class II**

Applications Industry & logistics · Sports facilities

Product summary

LED Brands	CREE / Samsung / Osram / Philips	**Driver**	Philips ENEC-certified LED driver
Efficacy (lm/W)	110–130 lm/W	**Coating Colour**	RAL Code 9006 (Optional)
Electrical Protection Class	Class I / Class II	**Standards Compliance**	EN 60598-2-5; EN 60598-1

Production can be tailored to special demands.

Technical specifications

LED MODULE

CRI	>70 / >80 (Optional)
Colour Temperature CCT	3000 K / 4000 K / 6500 K (Optional)
Light Source	High Power LED
LED Life	50,000 hours
Optical Light Distribution	Symmetric / Asymmetric (Optional)
Mounting Console	Included

ELECTRICAL AND DRIVER PROPERTIES

Input Voltage	220–240 V AC, 50–60 Hz
Power Factor	>0.95
Dimming / Control Interfaces	Step Dim; 1–10 V; DALI; Zhaga Socket
Driver	Philips ENEC-certified LED driver

Dimensions (a × b × c)	300 × 260 × 15 mm

MECHANICAL AND DIMENSION PROPERTIES

Housing	Aluminium
IK	IK09
IP	IP66
Diffuser - Front Cover	PMMA Lens
Gasket	Silicone gasket
Mounting Console	Included
Paint RAL Code	9006 / Any RAL Code

Variants

Code	Power (W)	Luminous Flux (lm)	Efficacy (lm/W)
3MFL.FL.00.120	120	13200	110
3MFL.FL.01.150	150	16500	110
3MFL.FL.02.120	120	14400	120
3MFL.FL.03.150	150	18000	120
3MFL.FL.04.120	120	15600	130
3MFL.FL.05.150	150	19500	130

Standards & certifications

TSE · CE · EAC · ENEC · EMC · IP66 · IK09 · Class I / Class II

Standards compliance: EN 60598-2-5; EN 60598-1

Full product page and quotation request: **https://solarstreetlighting.net/en/products/floodlights/fl-m/floodlights-3m/**