LuXLuminaire Lighting solutions
A MIR GROUP COMPANY

PRODUCT DATASHEET
REV. 2026-11-12



LED FLOODLIGHTS · DYNAMICS FLOODLIGHTS

Dynamics Floodlight 1×8

Modular high-power floodlight in 16 sizes, from 1×1 to 3×16 LED modules.

POWER **350–400 W**	LUMINOUS FLUX **35000–52000 lm**	EFFICACY **100–130 lm/W**	INGRESS **IP66**
IMPACT **IK09**	COLOUR TEMP. **3000 K / 4000 K / 6500 K**	LED LIFE **50,000 hours**	ELECTRICAL CLASS **Class I / Class II**

Applications Sports facilities · Industry & logistics

Product summary

LED Brands	CREE / Samsung / Osram / Philips	**Driver**	Philips ENEC-certified LED driver
Efficacy (lm/W)	100–130 lm/W	**Coating Colour**	RAL Code 9006 (Optional)
Electrical Protection Class	Class I / Class II	**Standards Compliance**	EN 60598-2-5; EN 60598-1

Production can be tailored to special demands.

Technical specifications

LED MODULE

CRI	>70 / >80 (Optional)
Colour Temperature CCT	3000 K / 4000 K / 6500 K (Optional)
Light Source	High Power LED
LED Life	50,000 hours
Optical Light Distribution	Symmetric / Asymmetric (Optional)
Mounting Console	Included

ELECTRICAL AND DRIVER PROPERTIES

Input Voltage	220–240 V AC, 50–60 Hz
Power Factor	>0.95
Dimming / Control Interfaces	Step Dim; 1–10 V; DALI; Zhaga Socket
Driver	Philips ENEC-certified LED driver

Dimensions (a × b × c)	627 × 245 × 120 mm

MECHANICAL AND DIMENSION PROPERTIES

Housing	Aluminium
IK	IK09
IP	IP66
Diffuser - Front Cover	PMMA Lens
Gasket	Silicone gasket
Mounting Console	Included
Paint RAL Code	9006 / Any RAL Code

Variants

Code	Power (W)	Luminous Flux (lm)	Efficacy (lm/W)
1X8M.FL.00.350	350	35000	100
1X8M.FL.01.400	400	40000	100
1X8M.FL.02.350	350	38500	110
1X8M.FL.03.400	400	44000	110
1X8M.FL.04.350	350	42000	120
1X8M.FL.05.400	400	48000	120
1X8M.FL.06.350	350	45500	130
1X8M.FL.07.400	400	52000	130

Standards & certifications

TSE · CE · EAC · ENEC · EMC · IP66 · IK09 · Class I / Class II

Standards compliance: EN 60598-2-5; EN 60598-1

Full product page and quotation request: **https://solarstreetlighting.net/en/products/floodlights/dynamics/floodlights-dynamics-1×8/**