LuXLuminaire Lighting solutions
A MIR GROUP COMPANY

PRODUCT DATASHEET
REV. 2026-11-12



LED FLOODLIGHTS · LUXPRO FLOODLIGHTS

Luxpro Floodlight 4

Compact Luxpro floodlights in five sizes for façades, yards and signage.

POWER **120–200 W**	LUMINOUS FLUX **13200–26000 lm**	EFFICACY **110–130 lm/W**	INGRESS **IP66**
IMPACT **IK09**	COLOUR TEMP. **3000 K / 4000 K / 6500 K**	LED LIFE **50,000 hours**	ELECTRICAL CLASS **Class I / Class II**

Applications Industry & logistics

Product summary

LED Brands	CREE / Samsung / Osram / Philips	**Driver**	Philips ENEC-certified LED driver
Efficacy (lm/W)	110–130 lm/W	**Coating Colour**	RAL Code 9006 (Optional)
Electrical Protection Class	Class I / Class II	**Standards Compliance**	EN 60598-2-5; EN 60598-1

Production can be tailored to special demands.

Technical specifications

LED MODULE

CRI	>70 / >80 (Optional)
Colour Temperature CCT	3000 K / 4000 K / 6500 K (Optional)
Light Source	High Power LED
LED Life	50,000 hours
Optical Light Distribution	Symmetric / Asymmetric (Optional)
Mounting Console	Included

ELECTRICAL AND DRIVER PROPERTIES

Input Voltage	220–240 V AC, 50–60 Hz
Power Factor	>0.95
Dimming / Control Interfaces	Step Dim; 1–10 V; DALI; Zhaga Socket
Driver	Philips ENEC-certified LED driver

Dimensions (a × b × c)	373 × 292 × 43 mm

MECHANICAL AND DIMENSION PROPERTIES

Housing	Aluminium
IK	IK09
IP	IP66
Diffuser - Front Cover	4 mm Tempered Glass
Gasket	Silicone gasket
Mounting Console	Included
Paint RAL Code	9006 / Any RAL Code

Variants

Code	Power (W)	Luminous Flux (lm)	Efficacy (lm/W)
LUX4.FL.00.120	120	13200	110
LUX4.FL.01.150	150	16500	110
LUX4.FL.02.180	180	19800	110
LUX4.FL.03.200	200	22000	110
LUX4.FL.04.120	120	14400	120
LUX4.FL.05.150	150	18000	120
LUX4.FL.06.180	180	21600	120
LUX4.FL.07.200	200	24000	120
LUX4.FL.08.120	120	15600	130
LUX4.FL.09.150	150	19500	130
LUX4.FL.10.180	180	23400	130
LUX4.FL.11.200	200	26000	130

Standards & certifications

TSE · CE · EAC · ENEC · EMC · IP66 · IK09 · Class I / Class II

Standards compliance: EN 60598-2-5; EN 60598-1

Full product page and quotation request: **https://solarstreetlighting.net/en/products/floodlights/luxpro/floodlights-luxpro-4/**